

DX1204DC

DX1204DCA



3 Axis - Easy to Adjust

Model	DX 1204DC	DX1204DCA
Pick Up Element	SHARP 1/4" CCD	
Effective Picture Elements(H*V)	NTSC:510*492, PAL:500*582	
Horizontal Resolution	420 TV Lines	
S/N Ratio	More than48dB	
Clock Frequency (MHZ)	NTSC:19.0699 , PAL :19.3125	
Scanning System	2:1 interlace	
Minimum Illumination	1.0 Lux@F2.0	
Synchronous System	Internal, Negative Sync.	
Auto Electronic Shutter	NTSC:1/60s~1/100.000s,PAL:1/50s~1/100,000s	
Gamma Characteristic	0.45	
Iris Control	Video/DC iris	
White Balance	Auto	
Back Light Compensation	ON/OFF (optional)	
Video Output	1Vpp,75 Ω	
Auto Gain Control	Auto	
Power/Current	12VDC(+/-10%)/120mA	
Lens	C/CS	
Dimension (mm)	75*100*100	
Weight (g)	270g	
Storage Temperature	-20C to +70C , Humidity:within 70% RH	
Operation Temperature	-10C to +50C , Humidity:within 90% RH	
Audio	NO	/ YES